



**WHERE
PRECISION
DRIVES
PRODUCTION**



SYSTEM SPECIFICATIONS

WETTED COMPONENTS:

Valve

- Delrin®
- Teflon®
- Polyethylene

Tank

- Stainless Steel

Material Line

- UV Safe Teflon®

MAXIMUM MATERIAL PRESSURE:

70 PSI

TANK VOLUME:

1 Gallon Maximum

DISPENSE MODE:

Manual

VALVE TIP:

Plastic Luer-Lok™ Adapter

OPERATING AIR PRESSURE:

None

SUPPLY VOLTAGE:

None

CAM200-1G-1


Description of System Operation:

1. Material is poured into stainless steel pressure pot.
2. Air pressure is applied to material.
3. Lever on valve is depressed to begin dispense.
4. Fluid pressure is adjusted to control flow.
5. Stroke adjuster on valve can be adjusted for flow rate.

For more information on PVA's dispensing capabilities, please contact one of our sales representatives at (518) 371-2684.

PVA also offers optional accessories for this system.

- ▲ Solvent stand to hold valve tip in solvent
- ▲ CAM2-SP, valve spare parts kit
- ▲ B62-0761-SP, system spare parts kit



15 Solar Drive
Halfmoon NY 12065
tel 518 371 2684
fx 518 371 2688
info@pva.net

Luer-Lok™ is a Becton Dickinson and Co. trademark.
Delrin® and Teflon® are registered trademarks of DuPont.