

Material Safety Data Sheet

Revision Date Prepared by Technical Information

Jan 26th, 2006 Howard Clark 1-800-201-8822 or <u>support@mgchemicals.com</u>

Head Office Emergency

9347 - 193 Street, Surrey, B.C., V4N 4E7 Phone Canutech (613) 996-6666 Collect 24 hrs

For updates please download from www.mgchemicals.com or fax requests to 1-800-708-9888

Section 1: Product Identification

MSDS Code: 834 - liquid Name: Liquid Flux

Related Part Numbers: 834-125ML; 834-1L; 834-4L

Use: Soldering flux for high temperature applications.

Section 2: Hazardous Ingredients

CAS#	Chemical Name	Percentage by weight	ACGIH TWA	Osha Pel	Osha Stel
67-63-0	2-propanal	50 – 100%	200ppm	400ppm	500ppm
110-15-6	succinic acid	< 2.5%	n/e	n/e	n/e

Section 3: Hazards Identification

WHMIS Codes: B2, D2B

NFPA Ratings: Health 1 Flammability 3 Reactivity 0

HMIS Ratings: Health 1 Flammability 4 Reactivity 0

Eyes: May cause eye irritation, characterized by a burning sensation, redness, tearing, inflammation, and

possible corneal injury.

Skin: May cause skin irritation with pain and stinging, especially if skin is abraded.

Inhalation: May cause respiratory tract irritation. Inhaling high concentrations may cause central nervous

system effects characterized by headache, and dizziness.

Ingestion: Harmful if swallowed. May cause gastrointestinal irritation with nausea, vomiting, and diarrhea. May

cause central nervous system depression.

Chronic: No effects known.

Section 4: First Aid Measure

Eyes: Remove contact lenses. Flush with water or saline for 20 minutes. Get medical aid.

Skin: Wash skin with large amounts of soap and water. Get medical aid if symptoms persist.

Inhalation: Immediately remove from exposure to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen. Get medical aid.

Ingestion: Do not induce vomiting. If conscious, give 1-2 glasses of water. Get medical aid.

Section 5: Fire Fighting Measures

Autoignition Temperature: 425°C Flash Point: 13°C LEL / UEL: 2 / 12

Extinguishing Media: CO2, sand, or extinguishing powder; do not use water

General Information: Will burn if involved in a fire.



Section 6: Accidental Release Measures

Spill Remove all sources of ignition. Provide adequate ventilation. Wear appropriate personal protection.

Procedure: Sprinkle absorbent compound onto spill, then sweep into a plastic or metal container. Wipe up further

residue with paper towel and place in container. Wash spill area with soap and water.

Section 7: Handling and Storage

Handling: Wash thoroughly after handling. Avoid contact with eyes, skin, and clothing. Do not ingest or inhale. Do

not expose container to heat or flame.

Keep away from sources of ignition. Store in a cool, dry, well ventilated area, away from incompatible Storage:

substances.

Section 8: Exposure Controls

Routes of

Eyes, ingestion, inhalation, and skin.

entry:

Ventilation: Use adequate general or local exhaust ventilation to keep airborne concentrations below exposure

limits.

Personal

Wear appropriate protective eyeglasses or chemical safety goggles. Wear appropriate protective

clothing to prevent skin contact. Use a NIOSH approved respirator when necessary. Protection:

Section 9: Physical and Chemical Properties

Physical liquid Odor: alcohol Solubility: 50% in **Evaporation** 1.9 State:

water Rate: (ether=1)

Boiling 82°C Specific 0.785 1 PSI Vapor 1.8 **pH**: 3 Vapor

Point: Gravity: Pressure: @21°C Density: (Air=1)

Section 10: Stability and Reactivity

Stability: Stable at normal temperatures and pressures.

Conditions to Temperatures over 40°C, ignition sources, and incompatible materials. Exposure to moist

avoid: air or water.

Incompatibilities: Strong oxidizers, strong acids

Polymerization: Will not occur.

Decomposition: carbon dioxide, carbon monoxide.

Section 11: Toxicological Information

Sensitization: (effects of repeated exposure) Not known to.

Carcinogenicity: (risk of cancer) Not known to.

Teratogenicity: (risk of malformation in an Not known to.

unborn fetus)

Reproductive Toxicity: (risk of sterility) Not known to.

Mutangenicity: (risk of heritable genetic effects) Not known to.

Lethal Exposure Ingestion(LD50): 6.5 g/kg Inhalation (LC50): 20 g/kg Skin (LD50): n/e

Concentrations:



Section 12: Ecological Information

General Avoid runoff into storms and sewers that lead into waterways. Water runoff can cause

Information: environmental damage.

Environmental Impact Data: (percentage by weight)

CFC: 0 HFC: 0 CI.Solv.: 0 VOC: 765 grams / liter HCFC: 0 ODP: 0

Section 13: Disposal Information

General Dispose of in accordance with all local, provincial, state, and federal regulations. Water runoff

Information: can cause environmental damage.

Section 14: Transportation Information

Ground: (all sizes 1 litre or less)

Consumer Commodity, ORM-D

Ground: (all sizes larger than 1 litre)

Shipping name—Isopropanol (Isopropyl Alcohol) Mixture, Class 3 Flammable Liquids, UN#1219, Packing Group II. Shipper must be trained and certified. Refer to CFR 49, TDG regulations (Canada).

Air:

Shipper must be trained and certified. Refer to IATA regulations.

Sea

Class 3, UN#1987, Packing Group II. Shipper must be trained and certified. Refer to IMDG regulations.

Section 15: Regulatory Information

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all of the information required by the Controlled Products Regulations.

SARA (Superfund Amendments and Reauthorization Act of 1986, USA, 40 CFR 372.4)

None of the chemicals in this product have a reportable quantity.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45

This product does not contain any chemicals subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depletors.

This product does not contain any class 2 ozone depletors.

This product does not contain any chemicals listed as hazardous air pollutants.

California Proposition 65 (Chemicals know to cause cancer or reproductive toxicity, May 1, 1997 revision, USA) This product does not contain any chemicals listed.

Health Canada:

Labeling and containers used in this product are listed in compliance with Consumer Chemicals and Container regulations.

Environment Canada:

Chemicals in this product are listed on the Domestic Substances List in the Canadian Environmental Protection Act This product does not contain any ozone depleting substances.

Industry and Science Canada:

Labeling, product identity, net quantity declaration, minimum printing type size heights, and packaging of this product is in compliance with the Consumer Packaging and Labeling Act and Regulations. This product is not slack filled in accordance to chapter 4 prohibitions.

RoHS (The restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2004).

This product is RoHS compliant.

PAGE 3 / 4 MSDS Code: 835 - liquid



Section 16: Other Information

Definitions: n/a = not applicable, n/e = not established

Disclaimer: This material safety data sheet is provided as an information resource only. M.G. Chemicals believes the

information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to verify its validity. The buyer assumes all responsibility of using and handling the product in

accordance with federal, state, and local regulations.

PAGE 4 / 4 MSDS Code: 835 - liquid